


REV	ZONE	REVISION	DATE

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S. T:0.30	GOLD PLATED	2
2	INSERT RING	PBT G.F.	WHITE,RED	2
3	INSULATOR	PBT G.F.	WHITE	2
4	CENTER PIN	BRASS T:0.25	GOLD PLATED	2
5	FRAME	C.R.S. T:0.60	GOLD PLATED	1



Specification:
 Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3-3.0 Kg.
 Extraction Force: 0.3-3.0 Kg.



 KUON YI INDUSTRIAL CORP. 崑義實業股份有限公司	COMPUTER NO.			UNIT	SCALE	PART NAME	
	D:\DWG\RJ-3313GG(W.R)-L			mm	1:1	RCA JACK	
	APPD.	CKD.	DWG.	DATE	TOLERANCE	PART NO.	REV.
MODEL	RJ-3313GG(W.R)-L	PAGE 1 OF 1	TINA	27-12-07	X. ±0.38 X ±0.25 XX ±0.13 XXX ±0.05		A0